



Przyłącze Proste Z Uszczelnieniem Tn 92 Gg Seria Lr, Sr Standard

Liczba wariantów: 20



ZESKANUJ MNIE

Warianty produktu

R Numer zamówieniowy	Seria	Ø d1 mm	Ciśnienie pracy bar	I mm	L mm	L1 mm	CH1 mm	R Ø F cal	R Ø N mm	R CH2 mm	M Ø F mm	R Ø N mm	M CH2 mm
IS-092GGRLO06	L	6	315	8	23	8,5	14	1/8'	14	14	10x1	14	14
IS-092GGRLO08	L	8	315	12	25	10	17	1/4'	19	19	12x1,5	17	17
IS-092GGRLO10	L	10	315	12	26	11	19	1/4'	19	19	14x1,5	19	19
IS-092GGRLO12	L	12	315	12	27	12,5	22	3/8'	22	22	16x1,5	22	22
IS-092GGRLO15	L	15	315	14	29	14	27	1/2'	27	27	18x1,5	24	24
IS-092GGRLO18	L	18	315	14	31	14,5	32	1/2'	27	27	22x1,5	27	27
IS-092GGRLO22	L	22	160	16	33	16,5	36	3/4'	32	32	26x1,5	32	32
IS-092GGRLO28	L	28	160	18	34	17,5	41	1'	40	41	33x2	40	41
IS-092GGRLO35	L	35	160	20	39	17,5	50	1 1/4'	50	50	42x2	50	50
IS-092GGRLO42	L	42	160	22	42	19	60	1 1/2'	55	55	48x2	55	55
IS-092GGRSO06	S	6	630	12	28	13	17	1/4'	19	19	12x1,5	17	17
IS-092GGRSO08	S	8	630	12	30	15	19	1/4'	19	19	14x1,5	19	19

R Numer zamówieniowy	Seria	Ø d1 mm	Ciśnienie pracy bar	I mm	L mm	L1 mm	CH1 mm	R Ø F cal	R Ø N mm	R CH2 mm	M Ø F mm	R Ø N mm	M CH2 mm
IS-092GGRSO10	S	10	630	12	31	15	22	3/8'	22	22	16x1,5	22	22
IS-092GGRSO12	S	12	630	12	33	17	24	3/8'	22	22	18x1,5	24	24
IS-092GGRSO14	S	14	630	14	37	19	27	1/2'	27	27	20x1,5	26	27
IS-092GGRSO16	S	16	400	14	37	18,5	30	1/2'	27	27	22x1,5	27	27
IS-092GGRSO20	S	20	400	16	42	20,5	36	3/4'	32	32	27x2	32	32
IS-092GGRSO25	S	25	400	18	47	23	46	1'	40	41	33x2	40	41
IS-092GGRSO30	S	30	400	20	50	23,5	50	1 1/4'	50	50	42x2	50	50
IS-092GGRSO38	S	38	315	22	57	26	60	1 1/2'	55	55	48x2	55	55