



Przyłącze Proste Z Uszczelnieniem Tn 92 Gg Seria Lr, Sr Niestandardowe

Liczba wariantów: 33



ZESKANUJ MNIE

Warianty produktu

Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	I mm	L mm	L1 mm	CH1 mm	R F cal	R N mm	R CH2 mm	Seria
1S-S92GGRL06B	6	315	12	25	10	14	1/4'	19	19	L
1S-S92GGRL06C	6	315	12	26	11,5	14	3/8'	22	22	L
1S-S92GGRL08A	8	315	8	24	8,5	17	1/8'	14	14	L
1S-S92GGRL08C	8	315	12	26	11,5	17	3/8'	22	22	L
1S-S92GGRL08D	8	315	14	27	12	17	1/2'	27	27	L
L	10	315	12	27	12	19	-	-	-	
1S-S92GGRL10D	10	315	14	28	13	19	1/2'	27	27	L
1S-092GGRL12B	12	315	12	26	12	22	1/4'	19	19	L
L	12	315	12	27	12,5	22	-	-	-	
1S-092GGRL12D	12	315	14	28	13	22	1/2'	27	27	L
1S-092GGRL15C	15	315	12	29	13,5	27	3/8'	22	24	L
1S-S92GGRL15F	15	315	16	30	15	27	3/4'	32	32	L

Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	I mm	L mm	L1 mm	CH1 mm	R F cal	R N mm	R CH2 mm	Seria
L	15	315	14	30	15	27	-	-	-	
1S-S92GGRL18F	18	315	16	30	14,5	32	3/4'	32	32	L
1S-S92GGRL18H	18	315	12	27	12,5	32	1'	-	-	L
1S-S92GGRL22D	22	160	14	33	16,5	36	1/2'	27	32	L
1S-092GGRL22H	22	160	18	34	17,5	36	1'	40	41	L
1S-S92GGRL28F	28	160	16	34	17,5	41	3/4'	32	41	L
1S-S92GGRL35H	35	160	18	39	17,5	50	1'	40	46	L
1S-S92GGRS08C	8	630	12	30	15,5	19	3/8'	22	22	S
1S-S92GGRS10B	10	630	12	31	14,5	22	1/4'	19	19	S
1S-S92GGRS10D	10	630	14	34	17,5	22	1/2'	27	27	S
1S-S92GGRS12B	12	630	12	33	16,5	24	1/4'	19	22	S
1S-S92GGRS12D	12	630	14	34	17,5	24	1/2'	27	27	S
1S-S92GGRS14C	14	630	12	36	18,5	27	3/8'	22	24	S
1S-092GGRS16C	16	400	12	36	18	30	3/8'	22	27	S

Seria	Średnica rury d1 mm	Ciśnienie pracy PN bar	I mm	L mm	L1 mm	CH1 mm	R F cal	R N mm	R CH2 mm	Seria
1S-S92GGRS16F	16	400	16	39	20,5	30	3/4'	32	32	S
1S-092GGRS20D	20	400	14	42	20,5	36	1/2'	27	32	S
1S-092GGRS25F	25	400	16	47	23	46	3/4'	32	41	S
1S-092GGRS30H	30	400	18	50	23,5	50	1'	40	46	S
1S-092GGRS38L	38	315	20	57	26	60	1 1/4'	50	55	S
1S-092GGRL12F B	12	315	14	26	14,5	22	3/4'	32	32	L
1S-092GGRS25G	25						1 1/4'			S