



## Złącze Proste Typ: Tn 98

Liczba wariantów: **25**

Złączki z końcówką T = zamiennik



ZESKANUJ MNIE

## Warianty produktu

| Numer zamówieniowy | Seria | Średnica rury<br>d1 mm | Ciśnienie<br>pracy PN bar | L mm | L1 mm | CH1 mm | CH3 mm | Waga 100<br>szt. kg |
|--------------------|-------|------------------------|---------------------------|------|-------|--------|--------|---------------------|
| 1AX098NLL04        | LL    | 4                      | 100                       | 31   | 12    | 10     | 9      | 1.5                 |
| 1AX098NLL06        | LL    | 6                      | 100                       | 32   | 9     | 12     | 11     | 2.2                 |
| 1AX098NLL08        | LL    | 8                      | 100                       | 35   | 12    | 14     | 12     | 2.8                 |
| 1AX098NLL10        | LL    | 10                     | 100                       | 35   | 12    | 17     | 14     | 4.5                 |
| 1AX098NLL12        | LL    | 12                     | 100                       | 35   | 11    | 19     | 17     | 6.0                 |
| 1BX098NLO06        | L     | 6                      | 315                       | 39   | 10    | 14     | 12     | 3.6                 |
| 1BX098NLO08        | L     | 8                      | 315                       | 40   | 11    | 17     | 14     | 5.0                 |
| 1BX098NLO10        | L     | 10                     | 315                       | 42   | 13    | 19     | 17     | 7.0                 |
| 1BX098NLO12        | L     | 12                     | 315                       | 43   | 14    | 22     | 19     | 8.7                 |
| 1BX098NLO15        | L     | 15                     | 315                       | 46   | 16    | 27     | 24     | 14                  |
| 1BX098NLO18        | L     | 18                     | 315                       | 48   | 16    | 32     | 27     | 20                  |
| 1BX098NLO22        | L     | 22                     | 160                       | 52   | 20    | 36     | 32     | 26.5                |
| 1BX098NLO28        | L     | 28                     | 160                       | 54   | 21    | 41     | 41     | 32                  |

| Numer zamówieniowy | Seria | Średnica rury<br>d1 mm | Ciśnienie<br>pracy PN bar | L mm | L1 mm | CH1 mm | CH3 mm | Waga 100<br>szt. kg |
|--------------------|-------|------------------------|---------------------------|------|-------|--------|--------|---------------------|
| IBX098NLO35        | L     | 35                     | 160                       | 63   | 20    | 50     | 46     | 50                  |
| IBX098NLO42        | L     | 42                     | 160                       | 66   | 21    | 60     | 55     | 74.1                |
| IBX098NSO06        | S     | 6                      | 630                       | 45   | 16    | 17     | 14     | 4.1                 |
| IBX098NSO08        | S     | 8                      | 630                       | 47   | 18    | 19     | 17     | 6.1                 |
| IBX098NSO10        | S     | 10                     | 630                       | 49   | 17    | 22     | 19     | 8.0                 |
| IBX098NSO12        | S     | 12                     | 630                       | 51   | 19    | 24     | 22     | 11.5                |
| IBX098NSO14        | S     | 14                     | 630                       | 57   | 22    | 27     | 24     | 18                  |
| IBX098NSO16        | S     | 16                     | 400                       | 57   | 21    | 30     | 27     | 23                  |
| IBX098NSO20        | S     | 20                     | 400                       | 66   | 23    | 36     | 32     | 35                  |
| IBX098NSO25        | S     | 25                     | 400                       | 74   | 26    | 46     | 41     | 68                  |
| IBX098NSO30        | S     | 30                     | 400                       | 80   | 27    | 50     | 46     | 83                  |
| IBX098NSO38        | S     | 38                     | 315                       | 90   | 29    | 60     | 55     | 121                 |