




Złącze Proste Redukcyjne Typ: Tn 98 R

Liczba wariantów: **36**

Kod z końcówką T = zamiennik



ZESKANUJ MNIE

Warianty produktu

Numer zamówieniowy	Seria	Średnica rury d1 mm	Średnica rury d2 mm	Ciśnienie pracy PN bar	L mm	L1 mm	CH1 mm	CH2 mm	CH3 mm	Waga 100 szt. kg
IBX098SLO0806	L	8	6	315	39,5	11,0	17	14	14	4,3
IBX098SLO1006	L	10	6	315	40,5	11,5	19	14	17	5,3
IBX098SLO1008	L	10	8	315	41,0	11,5	19	17	17	6,0
IBX098SLO1206	L	12	6	315	41,0	12,5	22	14	19	6,2
IBX098SLO1208	L	12	8	315	41,5	12,5	22	17	19	6,9
IBX098SLO1210	L	12	10	315	42,5	13,5	22	19	19	7,9
IBX098SLO1510	L	15	10	315	44,0	14,5	27	19	24	10,5
IBX098SLO1512	L	15	12	315	44,5	14,5	27	22	24	11,4
IBX098SLO1810	L	18	10	315	45,0	15,0	32	19	27	13,5
IBX098SLO1812	L	18	12	315	45,5	15,0	32	22	27	14,4
IBX098SLO1815	L	18	15	315	47,0	16,5	32	27	27	17,0
IBX098SLO2212	L	22	12	160	47,5	17,0	36	22	32	17,6
IBX098SLO2215	L	22	15	160	49,0	18,5	36	27	32	20,3

Numer zamówieniowy	Seria	Średnica rury d1 mm	Średnica rury d2 mm	Ciśnienie pracy PN bar	L mm	L1 mm	CH1 mm	CH2 mm	CH3 mm	Waga 100 szt. kg
IBX098SLO2218	L	22	18	160	50,0	18,0	36	32	32	23,3
IBX098SLO2818	L	28	18	160	51,0	19,0	41	32	41	26,0
IBX098SLO2822	L	28	22	160	53,0	21,0	41	36	41	29,3
IBX098SLO3522	L	35	22	160	57,5	21,0	50	36	46	38,3
IBX098SLO3528	L	35	28	160	58,5	21,0	50	41	46	41,0
IBX098SSO0806	S	8	6	630	46,0	18,0	19	17	17	5,1
IBX098SSO1006	S	10	6	630	47,0	17,5	22	17	19	6,0
IBX098SSO1008	S	10	8	630	48,0	17,5	22	19	19	7,0
IBX098SSO1206	S	12	6	630	48,0	18,5	24	17	22	7,8
IBX098SSO1208	S	12	8	630	49,0	18,5	24	19	22	8,8
IBX098SSO1210	S	12	10	630	50,0	18,0	24	22	22	9,8
IBX098SSO1410	S	14	10	630	53,0	20,5	27	22	24	13,0
IBX098SSO1412	S	14	12	630	54,0	20,5	27	24	24	14,8
IBX098SSO1612	S	16	12	400	54,0	21,0	30	24	27	17,3
IBX098SSO1614	S	16	14	400	57,0	22,5	30	27	27	20,5

Numer zamówieniowy	Seria	Średnica rury d1 mm	Średnica rury d2 mm	Ciśnienie pracy PN bar	L mm	L1 mm	CH1 mm	CH2 mm	CH3 mm	Waga 100 szt. kg
IBX098SSO2010	S	20	10	400	57,5	23,0	36	22	32	21,5
IBX098SSO2012	S	20	12	400	58,5	23,0	36	24	32	23,3
IBX098SSO2016	S	20	16	400	61,5	24,0	36	30	32	29,0
IBX098SSO2516	S	25	16	400	65,5	27,5	46	30	41	45,5
IBX098SSO2520	S	25	20	400	70,0	25,5	46	36	41	51,5
IBX098SSO3020	S	30	20	400	73,0	28,0	50	36	46	59,0
IBX098SSO3025	S	30	25	400	77,0	28,5	50	46	46	75,5
IBX098SSO3830	S	38	30	315	85,0	30,5	60	50	55	102