



Złącze Banjo Metryczne Z Uszczelnieniem Typ: Tn 111 Gg M

Liczba wariantów: **20**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	I mm	L mm	L10 mm	L11 mm	L12 mm	Ø N mm	CH1 mm	CH2 mm	CH mm	Ø F mm	Waga 100 szt. kg
IS-IIIIGGMLO06	L	6	315	8	28	13	12	27	15	14	17	19	10x1	6,5
IS-IIIIGGMLO08	L	8	315	12	29	14,5	14,5	30,5	18	17	19	22	22x1,5	10,5
IS-IIIIGGMLO10	L	10	315	12	30,5	15,5	14,5	30,5	20	19	19	22	14x1,5	12
IS-IIIIGGMLO12	L	12	315	12	34,5	19,5	16,5	37	22	22	24	30	16x1,5	20
IS-IIIIGGMLO15	L	15	315	14	38	22	20,5	44,5	24	27	24	32	18x1,5	27
IS-IIIIGGMLO18	L	18	315	14	39,5	22	21,5	47,5	28	32	27	36	22x1,5	36
IS-IIIIGGMLO22	L	22	160	16	46	28	24,5	55,5	32	36	32	41	26x1,5	56
IS-IIIIGGMLO28	L	28	160	18	50	31,5	30,5	68	40	41	41	50	33x2	93,5
IS-IIIIGGMLO35	L	35	160	20	59	35,5	35,5	79	50	50	50	60	42x2	152
IS-IIIIGGMLO42	L	42	160	22	66	41,5	40,5	90	56	60	55	70	48x2	234
IS-IIIIGGMSO06	S	6	400	12	31	16,5	14,5	30,5	18	17	19	22	12x1,5	10,5
IS-IIIIGGMSO08	S	8	400	12	31	16,5	14,5	30,5	20	19	19	22	14x1,5	13
IS-IIIIGGMSO10	S	10	400	12	36,5	20	16,5	37	22	22	24	30	16x1,5	22,5
IS-IIIIGGMSO12	S	12	400	12	36,5	20	17	37,5	24	24	24	30	18x1,5	23,5

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	I mm	L mm	L10 mm	L11 mm	L12 mm	Ø N mm	CH1 mm	CH2 mm	CH mm	Ø F mm	Waga 100 szt. kg
IS-III GGMSO14	S	14	400	14	42,5	23,5	21	46,5	26	27	27	36	20x1,5	34,5
IS-III GGMSO16	S	16	400	14	42,5	23,5	21,5	47,5	28	30	27	36	22x1,5	36,5
IS-III GGMSO20	S	20	400	16	51	27	24,5	55,5	33	36	32	41	27x2	64
IS-III GGMSO25	S	25	250	18	58	31	30,5	68	40	46	41	50	33x2	113,5
IS-III GGMSO30	S	30	250	20	66	36,5	35,5	79	50	50	50	60	42x2	173,5
IS-III GGMSO38	S	38	250	22	76	42,5	40,5	90	56	60	55	70	48x2	271,5