




## Przyłącze Proste Z Uszczelnieniem Typ: Tn 426 R

Liczba wariantów: 20

---



ZESKANUJ MNIE

**Warianty produktu**

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L1 mm	Ø F cal	l mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	O-Ring mm	Waga 100 szt. kg
1B-426RLO06	L	6	315	24,5	1/8'	8	14	14	12x1,5	14	4x1,5	2,5
1B-426RLO08	L	8	315	29,5	1/4'	12	19	19	14x1,5	17	6x1,5	4,3
1B-426RLO10	L	10	315	27,5	1/4'	12	19	19	16x1,5	19	7,5x1,5	4,8
1B-426RLO12	L	12	315	34	3/8'	12	22	22	18x1,5	22	9x1,5	6,9
1B-426RLO15	L	15	315	32	1/2'	14	27	27	22x1,5	27	12x2	12
1B-426RLO18	L	18	315	31,5	1/2'	14	27	27	26x1,5	32	15x2	13,5
1B-426RLO22	L	22	160	32,5	3/4'	16	32	32	30x2	36	20x2	19,5
1B-426RLO28	L	28	160	35	1'	18	41	40	36x2	41	26x2	36
1B-426RLO35	L	35	160	42,5	1 1/4'	20	50	50	45x2	50	32x2,5	45,5
1B-426RLO42	L	42	160	46,5	1 1/2'	22	55	55	52x2	60	38x2,5	66
1B-426RSO06	S	6	630	27	1/4'	12	19	19	14x1,5	17	4x1,5	4,5

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L1 mm	Ø F cal	l mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	O-Ring mm	Waga 100 szt. kg
1B-426RSO08	S	8	630	29,5	1/4'	12	19	19	16x1,5	19	6x1,5	5
1B-426RSO10	S	10	630	32	3/8'	12	22	22	18x1,5	22	7,5x1,5	7,5
1B-426RSO12	S	12	630	34	3/8'	12	22	22	20x1,5	24	9x1,5	8,2
1B-426RSO14	S	14	630	36,5	1/2'	14	27	27	22x1,5	27	10x2	12,5
1B-426RSO16	S	16	400	37	1/2'	14	27	27	24x1,5	30	12x2	14,5
1B-426RSO20	S	20	400	43	3/4'	16	32	32	30x2	36	16,3x2,4	22
1B-426RSO25	S	25	400	48	1'	18	41	40	36x2	46	20,3x2,4	40
1B-426RSO30	S	30	400	51	1 1/4'	20	50	50	42x2	50	25,3x2,4	58
1B-426RSO38	S	38	315	60	1 1/2'	22	55	55	52x2	60	33,3x2,4	78,5