




Przyłącze Proste Z Uszczelnieniem Typ: Tn 426 M

Liczba wariantów: 20



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L1 mm	Ø F mm	l mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	O-Ring mm	Waga 100 szt. kg
1B-426MLO06	L	6	315	24,5	10x1	8	14	14	12x1,5	14	4x1,5	2,3
1B-426MLO08	L	8	315	26,5	12x1,5	12	17	17	14x1,5	17	6x1,5	3,8
1B-426MLO10	L	10	315	27,5	14x1,5	12	19	19	16x1,5	19	7,5x1,5	4,8
1B-426MLO12	L	12	315	30,5	16x1,5	12	22	22	18x1,5	22	9x1,5	6,7
1B-426MLO15	L	15	315	31,5	18x1,5	12	24	24	22x1,5	27	12x2	10
1B-426MLO15	L	18	315	31,5	22x1,5	14	27	27	26x1,5	32	15x2	14
1B-426MLO22	L	22	160	32,5	26x1,5	16	32	32	30x2	36	20x2	20
1B-426MLO28	L	28	160	35	33x2	18	41	40	36x2	41	26x2	36
1B-426MLO35	L	35	160	42,5	42x2	20	50	50	45x2	50	32x2,5	45
1B-426MLO42	L	42	160	46,5	48x2	22	55	55	52x2	60	38x2,5	71
1B-426MSO06	S	6	630	27	12x1,5	12	17	17	14x1,5	17	4x1,5	4
1B-426MSO08	S	8	630	29,5	14x1,5	12	19	19	16x1,5	19	6x1,5	5

Nr katalogowy	Seria	Ø d1 mm	Ciśnienie pracy bar	L1 mm	Ø F mm	l mm	CH2 mm	Ø N mm	Ø F1 mm	CH1 mm	O-Ring mm	Waga 100 szt. kg
1B-426MSO10	S	10	630	32	16x1,5	12	22	22	18x1,5	22	7,5x1,5	7
1B-426MSO12	S	12	630	34	18x1,5	12	24	24	20x1,5	24	9x1,5	9
1B-426MSO14	S	14	630	36,5	20x1,5	14	27	26	22x1,5	27	10x2	12
1B-426MSO16	S	16	400	37	22x1,5	14	27	27	24x1,5	30	12x2	15
1B-426MSO20	S	20	400	43	27x2	16	32	32	30x2	36	16,3x2,4	22,3
1B-426MSO25	S	25	400	48	33x2	18	41	40	36x2	46	20,3x2,4	40
1B-426MSO30	S	30	400	51	42x2	20	50	50	42x2	50	25,3x2,4	58
1B-426MSO38	S	38	315	60	48x2	22	55	55	52x2	60	33,3x2,4	78