



Złącze Proste Z Nakrętką Odmiana Ciężka Typ: Tn 432 S

Liczba wariantów: **45**



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Seria	Ø D1 mm	Ø D2 mm	Ciśnienie pracy bar	L1 mm	L2 mm	CH2 mm	CH3 mm	Ø F1 mm	CH mm	O-Ring mm	Waga 100 szt. kg
1B-432SO0806	S	8	6	630	27	42	17	19	16x1,5	14	6x1,5	3,5
1B-432SO1006	S	10	6	630	27,5	42	17	22	18x1,5	17	7,5x1,5	7,1
1B-432SO1006	S	10	8	630	27,5	42	19	22	18x1,5	17	7,5x1,5	7,7
1B-432SO1206	S	12	6	630	29	44	17	24	20x1,5	17	9x1,5	8,2
1B-432SO1208	S	12	8	630	29	44	19	24	20x1,5	17	9x1,5	9,2
1B-432SO1210	S	12	10	630	29,5	46	22	24	20x1,5	19	9x1,5	10,7
1B-432SO1406	S	14	6	630	31,5	46	17	27	22x1,5	19	10x2	9,1
1B-432SO1408	S	14	8	630	31,5	46	19	27	22x1,5	19	10x2	10
1B-432SO1410	S	14	10	630	31	47	22	27	22x1,5	19	10x2	11
1B-432SO1412	S	14	12	630	31	47	24	27	22x1,5	22	10x2	12
1B-432SO1606	S	16	6	400	32	47	17	30	24x1,5	22	12x2	12,6
1B-432SO1608	S	16	8	400	32	47	19	30	24x1,5	22	12x2	14,7

Nr katalogowy	Seria	Ø D1 mm	Ø D2 mm	Ciśnienie pracy bar	L1 mm	L2 mm	CH2 mm	CH3 mm	Ø F1 mm	CH mm	O-Ring mm	Waga 100 szt. kg
1B-432SO1610	S	16	10	400	31,5	48	22	30	24x1,5	22	12x2	14,7
1B-432SO1612	S	16	12	400	31,5	48	24	30	24x1,5	22	12x2	15,5
1B-432SO1614	S	16	14	400	33	51	27	30	24x1,5	24	12x2	16,5
1B-432SO2006	S	20	6	400	36	51	17	36	30x2	27	16,3x2,4	19
1B-432SO2008	S	20	8	400	36	51	19	36	30x2	27	16,3x2,4	20,5
1B-432SO2010	S	20	10	400	35,5	52	22	36	30x2	27	16,3x2,4	20,5
1B-432SO2012	S	20	12	400	35,5	52	24	36	30x2	27	16,3x2,4	21,5
1B-432SO2014	S	20	14	400	37	55	27	36	30x2	27	16,3x2,4	23,5
1B-432SO2016	S	20	16	400	36,5	55	30	36	30x2	27	16,3x2,4	26
1B-432SO2506	S	25	6	400	38,5	53	17	46	36x2	32	20,3x2,4	31
1B-432SO2508	S	25	8	400	38,5	53	19	46	36x2	32	20,3x2,4	32
1B-432SO2510	S	25	10	400	38	54	22	46	36x2	32	20,3x2,4	33,5
1B-432SO2512	S	25	12	400	38	54	24	46	36x2	32	20,3x2,4	33,5
1B-432SO2514	S	25	14	400	39,5	57	27	46	36x2	32	20,3x2,4	35
1B-432SO2516	S	25	16	400	39	57	30	46	36x2	32	20,3x2,4	37,5

Nr katalogowy	Seria	Ø D1 mm	Ø D2 mm	Ciśnienie pracy bar	L1 mm	L2 mm	CH2 mm	CH3 mm	Ø F1 mm	CH mm	O-Ring mm	Waga 100 szt. kg
1B-432SO2520	S	25	20	400	39	61	36	46	36x2	32	20,3x2,4	43,5
1B-432SO3006	S	30	6	400	44	59	17	50	42x2	41	25,3x2,4	43
1B-432SO3008	S	30	8	400	44	59	19	50	42x2	41	25,3x2,4	43
1B-432SO3010	S	30	10	400	43,5	60	22	50	42x2	41	25,3x2,4	43,5
1B-432SO3012	S	30	12	400	43,5	60	24	50	42x2	41	25,3x2,4	44,5
1B-432SO3014	S	30	14	400	45	63	27	50	42x2	41	25,3x2,4	46
1B-432SO3016	S	30	16	400	44,5	63	30	50	42x2	41	25,3x2,4	48,8
1B-432SO3020	S	30	20	400	44,5	66	36	50	42x2	41	25,3x2,4	53,5
1B-432SO3025	S	30	25	400	45	69	46	50	42x2	41	25,3x2,4	67,5
1B-432SO3806	S	38	6	315	47,5	62	17	60	52x2	50	33,3x2,4	71
1B-432SO3808	S	38	8	315	47,5	62	19	60	52x2	50	33,3x2,4	71
1B-432SO3810	S	38	10	315	47	63	22	60	52x2	50	33,3x2,4	71,5
1B-432SO3812	S	38	12	315	47	63	24	60	52x2	50	33,3x2,4	72
1B-432SO3814	S	38	14	315	48,5	66	27	60	52x2	50	33,3x2,4	74,5
1B-432SO3816	S	38	16	315	48	66	30	60	52x2	50	33,3x2,4	77

Nr katalogowy	Seria	Ø D1 mm	Ø D2 mm	Ciśnienie pracy bar	L1 mm	L2 mm	CH2 mm	CH3 mm	Ø F1 mm	CH mm	O-Ring mm	Waga 100 szt. kg
1B-432SO3820	S	38	20	315	48	70	36	60	52x2	50	33,3x2,4	81
1B-432SO3825	S	38	25	315	48,5	73	46	60	52x2	50	33,3x2,4	85
1B-432SO3830	S	38	30	315	49	76	50	60	52x2	50	33,3x2,4	88