




Przyłącze Kątowe Typ: St. 36

Liczba wariantów: 15



ZESKANUJ MNIE

Warianty produktu

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
OO-ST360606	10	3/8'	9/16'	9/16'	21,1	29	10	14	17	350
OO-ST360808	12	1/2'	3/4'	3/4'	24,9	33	11	19	22	350
OO-ST360810	12	1/2'	3/4'	7/8'	24,9	38,6	12,5	22	27	350
OO-ST361010	14	-	7/8'	7/8'	28,2	38,6	12,5	22	27	350
OO-ST361008	-	-	7/8'	3/4'	-	-	-	22	27	350
OO-ST361010	16	5/8'	7/8'	7/8'	28,2	38,6	12,5	22	27	350
OO-ST361210	18	-	11/16'	7/8'	32,5	39,8	12,5	27	27	350
OO-ST361210	20	3/4'	11/16'	7/8'	32,5	39,8	12,5	27	27	350
OO-ST361212	18	-	11/16'	11/16'	32,5	43,9	15	27	32	350
OO-ST361212	20	3/4'	11/16'	11/16'	32,5	43,9	15	27	32	350
OO-ST361612	25	1'	15/16'	11/16'	37,3	43,9	15	33	32	350
OO-ST361616	25	1'	15/16'	15/16'	37,3	47,2	15	33	38	350
OO-ST361620	-	-	15/16	15/8'	-	-	-	-	-	-

Nr katalogowy	Ø R mm	Ø R cal	Ø R-UNF JIC 37° cal	Ø R2 UNF cal	B mm	B2 mm	C2 mm	CH mm	CH1 mm	Ciśnienie pracy bar
00-ST362020	32	1 1/4'	1 5/8'	1 5/8'	40,4	48,5	15	41	50	210
00-ST362424	38	1 1/2'	1 7/8'	1 7/8'	45,2	48,5	15	48	55	140