


Złącze Proste Bsp / Nakrętka Orfs Rk2160

Liczba wariantów: **19**



ZESKANUJ MNIE

Warianty produktu

Kod towaru	T Ø mm	T Ø cal	F	F1	A mm	B mm	D mm	D1 mm	CH mm	CH1 mm	Ciśnienie robocze bar	Ciśnienie max bar
RK2160-06-10	6	1/4	9/16-18	1/8-28	34	26,2	4,2	4,2	14	19	400	530
RK2160-06-13	6	1/4	9/16-18	1/4-19	38	26,2	4,2	4,2	19	19	400	530
RK2160-08-13	8	5/16	11/16-16	1/4-19	41	20,8	6,5	5	19	22	400	530
RK2160-08-17	8	5/16	11/16-16	3/8-19	40	28,2	6,5	6,5	22	22	400	530
RK2160-10-13	10	3/8	11/16-16	1/4-19	41	20,8	6,5	5	19	22	400	530
RK2160-10-17	10	3/8	11/16-16	3/8-19	40	28,2	6,5	6,5	22	22	400	530
RK2160-12-17	12	1/2	13/16-16	3/8-19	48	35,8	9	7,8	22	24	400	530
RK2160-12-21	12	1/2	13/16-16	1/2-14	49,5	35,5	9	9	27	24	400	530
RK2160-14-21	14	-	1-14	1/2-14	52	38	11,5	11,5	27	30	400	530
RK2160-15-21	15	-	1-14	1/2-14	52	38	11,5	11,5	27	30	400	530
RK2160-16-21	16	5/8	1-14	1/2-14	52	38	11,5	11,5	27	30	400	530
RK2160-18-26	18	-	1-3/16-12	3/4-14	57,4	41,4	14	14	32	36	400	530
RK2160-20-26	20	3/4	1-3/16-12	3/4-14	57,4	41,4	14	14	32	36	400	530

Kod towaru	T Ø mm	T Ø cal	F	F1	A mm	B mm	D mm	D1 mm	CH mm	CH1 mm	Ciśnienie robocze bar	Ciśnienie max bar
RK2160-22-33	22	-	1-7/16-12	1-11	67	49	20	20	41	46	400	530
RK2160-25-33	25	1	1-7/16-12	1-11	67	49	20	20	41	46	400	530
RK2160-28-42	28	-	1-11/16-12	1-1/4-11	69	49	26	25	50	50	250	330
RK2160-32-42	32	1 1/4	1-11/16-12	1-1/4-11	69	49	26	25	50	50	250	330
RK2160-35-48	35	-	2-12	1-1/2-11	72	49,8	32	32	55	60	250	330
RK2160-38-48	38	1 1/2	2-12	1-1/2-11	72	49,8	32	32	55	60	250	330