




Przyłącze Proste Z Uszczelnieniem Tn 92 Gg Seria Lm, Sm Standard

Liczba wariantów: **20**



ZESKANUJ MNIE

Warianty produktu

R Numer zamówieniowy	Seria	Ciśnienie pracy bar	M Ø F mm	Średnica rury d1 mm
1S-092GGMLO06	L	350	10x1	6
1S-092GGMLO08	L	420	12x1.5	8
1S-092GGMLO10	L	420	14x1.5	10
1S-092GGMLO12	L	420	16x1.5	12
1S-092GGMLO15	L	350	18x1.5	15
1S-092GGMLO18	L	350	22x1.5	18
1S-092GGMLO22	L	350	26x1.5	22
1S-092GGMLO28	L	280	33x2	28
1S-092GGMLO35	L	210	42x2	35
1S-092GGMLO42	L	210	48x2	42
1S-092GGMSO06	S	630	12x1.5	6
1S-092GGMSO08	S	630	14x1.5	8
1S-092GGMSO10	S	630	16x1.5	10
1S-092GGMSO12	S	630	18x1.5	12

R Numer zamówieniowy	Seria	Ciśnienie pracy bar	M Ø F mm	Średnica rury d1 mm
1S-092GGMSO14	S	630	20x1.5	14
1S-092GGMSO16	S	450	22x1.5	16
1S-092GGMSO20	S	420	27x2	20
1S-092GGMSO25	S	420	33x2	25
1S-092GGMSO30	S	420	42x2	30
1S-092GGMSO38	S	420	48x2	38